



Safe Handling – Methylamine (Monomethylamine)

NOTE:

Customers may need a valid DEA registration for the facility to which this product is to be delivered depending upon its usage

1. Product Description – Physical Properties:

Methylamine is a colorless, flammable liquefied gas with a characteristic fishy or ammonia type odor

Chemical Formula – CH_3NH_2

CAS 74-89-5 at 100% Volume

2. Specific Hazards

WARNING!

FLAMMABLE GAS

CONTENTS UNDER PRESSURE

HARMFUL IF SWALLOWED

CAUSES RESPIRATORY TRACT, EYE AND SKIN IRRITATION

CAUSES DAMAGE TO THE FOLLOWING ORGANS: RESPIRATORY TRACT, SKIN

EYES, EYE, LENS OR CORNEA, NOSE, SINUSES, THROAT

VAPOR MAY CAUSE FLASH FIRE

Do not ingest

Avoid contact with skin and clothing

Avoid breathing gas

Keep away from heat, sparks and flame

Do not puncture or incinerate container

Keep container closed

Use only with adequate ventilation

Wash thoroughly after handling.

3. Material Safety Data Sheet (MSDS)

Airgas MSDS # 1034 is available for download at www.airgas.com or ask your Airgas associate for a copy

4. First Aid

See MSDS

5. PPE

See MSDS



6. Shipping Description

If over 100 lbs. – UN 1061, Methylamine, Anhydrous, RQ, 2.1

If under 100 lbs. – UN 1061, Methylamine, Anhydrous, 2.1

Hazard Class – 2.1

Markings, Labels – Flammable Gas (2)

7. Available Containers:

Container	DOT Spec	Nominal Dimensions (D x L)	Average Tare (Lbs)	Average Internal Volume(ft ³)	Product Capacity (Lbs)
350 (A-1)	4BW240	16 x 50	75	3.83	125
½ Ton (A-5)	4BW240	30 x 57	315	16	550

NOTE: All Containers are shipped with a vapor (head) pressure of 29 psig at 70°

8. Valves

Type – CGA 705, With Washer, Hand wheel Operated (unless otherwise noted)

Connection Torque - 40 – 60 ft lbs

Configuration - All cylinders are configured with double valving to allow either liquid or gas withdrawal

Orientation - Valves are oriented in such a position to allow for ease of hook up

9. Pressure Relief Device (PRD)

A PRD is not required as per CGA S-1.1

10. Handling

CAUTION:

Cylinders should only be moved with a suitable fork lift

Do not ingest

Avoid contact with eyes, skin and clothing

Keep container closed

Use only with adequate ventilation

Keep away from heat, sparks and flame

To avoid fire, minimize ignition sources

Use explosion-proof electrical (ventilating, lighting and material handling) equipment

Do not puncture or incinerate container

Wash thoroughly after handling

High pressure gas

Use equipment rated for cylinder pressure

Close valve after each use and when empty

Protect cylinders from physical damage; do not drag, roll, slide, or drop

Use a suitable hand truck for cylinder movement

A-1 and A-5 Cylinders are equipped with a forklift base for ease of movement

11. Storage

Keep container tightly closed

Keep container in a cool, well-ventilated area

Cylinders should be stored upright, with valve protection cap in place, and firmly secured to prevent falling or being knocked over

Cylinder temperatures should not exceed 52 °C (125°F)

12. Recommended Equipment for Proper Usage:

- Stainless steel positive seal regulator, part number Y11-C444 with a maximum outlet pressure of 100 psig
- Line pressure relief valve rated to 110 psig maximum
- Check Valve (2) part number Y33-442 (Installed in-line)

NOTE:

Check valves should be put on a scheduled maintenance program to be replaced in intervals that are consistent with use but at least every six months

13. Hook Up Procedures:

CAUTION:

If nitrogen is used to pressurize cylinder for liquid withdrawal, a suitable safety device must be installed to prevent over pressurization of the cylinder. Also, a dual check valve configuration must be installed in the process line to prevent pressure back flow into the cylinder.

Do not exceed 100 psig (50– 100 psig is recommended) regulated nitrogen pressure to the cylinder.

FAILURE TO COMPLY CAN RESULT IN CATASTOPHIC CYLINDER OR LINE FAILURE

13.1 If withdrawing liquid with a nitrogen pad:

13.1.1 Insure valves are tightly closed

13.1.2 Remove Dust Caps from Valve Outlets

13.1.3 Install Regulator with Nitrogen Line to Vapor Valve – Install Washer and torque fitting to 40 – 60 ft lbs.

13.1.4 Install Product discharge line to liquid valve – Install Washer and torque fitting to 40 - 60 ft lbs

13.1.5 Slowly open liquid valve allowing product to fill the process line

13.1.6 Adjust nitrogen pressure to desired setting (see note above regarding maximum pressure)

13.1.7 Slowly open Vapor valve allowing nitrogen pressure to the cylinder

13.2 If withdrawing vapor only

- 13.2.1 Insure valve is tightly closed
- 13.2.2 Remove Dust Cap from Vapor Valve
- 13.2.3 Install Product discharge line to Vapor Valve – Install Washer and torque fitting to 40 - 60 ft lbs
- 13.2.4 Slowly open valve allowing product to fill the process line

14. Disconnect Procedures:

14.1 If withdrawing liquid with a nitrogen pad

- 14.1.1 Close Vapor Valve
- 14.1.2 Reduce regulated Nitrogen Line pressure to zero and depressurize line
- 14.1.3 Close Liquid Valve
- 14.1.4 Remove Nitrogen line and regulator – use caution as there may be residual pressure in the nitrogen line
- 14.1.5 Install Valve Dust Cap
- 14.1.6 Open Liquid valve and vent all residual cylinder pressure to appropriate receptacle
- 14.1.7 Close Liquid Valve
- 14.1.8 Install Valve Dust Cap

14.2 If withdrawing vapor only

- 14.2.1 Close Vapor Valve
- 14.2.2 Remove process line – use caution as there may be residual pressure and/or product in the line
- 14.2.3 Install Valve Dust Cap



Typical A-5 Cylinder Handling



Typical A-1 Cylinder Handling



Typical Valve Configuration (A-1, A-5 Cylinders)



This Safe Handling Brochure is provided by Airgas Specialty Gases, Inc. (“Airgas”) for information purposes only. This Brochure is provided with the understanding that Airgas and Airgas’ personnel are not engaged in rendering, legal, regulatory or other professional services. Airgas believes the information provided to be accurate as of the date of publication but assumes no liability for any damages in connection with the use of this Brochure. It is the responsibility of the user to determine the applicability of such information and recommendations and the suitability of any product for its own particular purpose.

Applicable safety and environmental laws, regulations and standards should be reviewed by the user along with the Material Safety Data Sheet (MSDS) for this product, which contains information on safe handling. Hazards, toxicity and behavior of the product may vary when used in other manufacturing settings. In all instances Airgas shall not be held liable for any improper or incorrect use of the information described and/or contained in the Brochure or any related training or information and assumes no responsibility for any user's use of such information and/or training. In no event shall Airgas or Airgas personnel be liable for any direct, indirect, incidental, special, exemplary, or consequential damages however caused and on any theory of liability, whether in contract, strict liability, or tort (including negligence or otherwise) arising in any way out of the use of these training materials and information. This disclaimer of liability applies to any damages or injury, including but not limited to those caused by any failure of performance, error, omission, completeness, or use of materials.

*Copyright © 2010 Airgas Specialty Gases, Inc. or an affiliate thereof
All rights reserved*